

# **Safety Data Sheet**

# prepared to UN GHS Revision 3

# 1. Identification of the Substance/Mixture and the Company/Undertaking

Base

1.1 Product Identifier 600 T RED Revision Date: 18/08/2016

Component of multi-component industrial grouts, mortars and screeds.

Product Name: Stonchem 600 Series Topcoat

Supercedes Date: New SDS

1.2 Relevant identified uses of the

substance or mixture and uses

advised against

1.3 Details of the supplier of the safety data sheet

Importer: None

Manufacturer: StonCor Africa (Pty.) Ltd.

8 Cresset Road

Midrand Industrial Park, Chloorkop

P.O. Box 2205 2001, Johannesburg South Africa

Regulatory / Technical Information:

+27 11 254 5500

Datasheet Produced by: Maritz, Rory - ehs@stoncor.com

**1.4 Emergency telephone number:** CHEMTREC 1-800-424-9300 (Inside US)

CHEMTREC +1 703 5273887 (Outside ÚS)

## 2. Hazard Identification

## 2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 2
Carcinogenicity, category 1A
Eye Irritation, category 2
STOT, repeated exposure, category 1
STOT, single exposure, category 2
STOT, single exposure, category 3, RTI
Skin Irritation, category 2
Skin Sensitizer, category 1

#### 2.2 Label elements

#### Symbol(s) of Product



#### Signal Word

Danger

#### Named Chemicals on Label

calcium oxide, silicon dioxide (amorphous), quartz (silicon dioxide), phenol, polymer with formaldehyde, glycidyl ether

#### **HAZARD STATEMENTS**

Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Carcinogenicity, category 1A	H350-1A	May cause cancer.
STOT, single exposure, category 2	H371	May cause damage to organs.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.
PRECAUTION PHRASES		
	P201	Obtain special instructions before use.
	P202	Do not handle until all safety precautions have been read and understood.
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P264	Wash hands thoroughly after handling.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P284	Wear respiratory protection

P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/
	face protection.
P284	Wear respiratory protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention.
D000 - D011	IF and and an if you feel would coll a DOLOGNI OFNITED and

P309+P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.
P314 Get medical advice/attention if you feel unwell.

P333+313 Get medical advice/attention if you feel unwell.

If skin irritation or rash occurs: Get medical advice/attention.

P391 Collect spillage.

## 2.3 Other hazards

No Information

#### Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

# 3. Composition/Information On Ingredients

### 3.2 Mixtures

#### **Hazardous Ingredients**

CAS-No.	Chemical Name	<u>%</u>
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	25-50
7631-86-9	silicon dioxide (amorphous)	25-50

14808-60-7	quartz (silicon dioxide)	2.5-10
12034-12-7	sodium superoxide	2.5-10
1309-37-1	red iron oxide	2.5-10
100-51-6	Benzyl alcohol	2.5-10
1305-78-8	calcium oxide	2.5-10
64742-95-6	Solvent naphtha (petroleum), light arom.	0.1-1.0
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	<0.1

CAS-No.	GHS Symbols	GHS Hazard Statements	M-Factors
28064-14-4	GHS07-GHS09	H315-317-319-411	0
7631-86-9	GHS07-GHS08	H335-372	0
14808-60-7	GHS08	H350-370	0
12034-12-7			0
1309-37-1			0
100-51-6	GHS07	H302-319-332	0
1305-78-8	GHS05-GHS07	H315-318-335	0
64742-95-6	GHS08-GHS09	H304-411	0
64742-82-1	GHS02-GHS07-GHS08-GHS09	H226-304-336-411	0

Additional Information:

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

#### 4. First-aid Measures

#### 4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Never give anything by mouth to an unconscious person.

#### Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

## 4.2 Most important symptoms and effects, both acute and delayed

No Information

#### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

# 5. Fire-fighting Measures

#### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

#### 5.2 Special hazards arising from the substance or mixture

No Information

## 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Water sprayDry powderAlcohol-resistant foamCarbon dioxide (CO2)High volume water jet. Hazardous decomposition products formed under fire conditions.

## 6. Accidental Release Measures

## 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

#### 6.2 Environmental precautions

No Information

#### 6.3 Methods and material for containment and cleaning up

No special environmental precautions required. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). After cleaning, flush away traces with water.

#### 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

#### 7. Handling and Storage

# 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING:** Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Avoid prolonged contact with eyes, skin and clothing.

**PROTECTION AND HYGIENE MEASURES:** When using, do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing.

#### 7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

STORAGE CONDITIONS: Keep tightly closed in a dry and cool place.

#### 7.3 Specific end use(s)

No specific advice for end use available.

## 8. Exposure Controls/Personal Protection

## 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (EU)

<u>Name</u>	CAS-No.	LTEL ppm	STEL ppm	STEL mg/ m3	<u>LTEL mg/</u> <u>m3</u>	OEL Note
phenol, polymer with formaldehyde, glycidyl ether	28064-14-4					
silicon dioxide (amorphous)	7631-86-9					
quartz (silicon dioxide)	14808-60-7					
sodium superoxide	12034-12-7					
red iron oxide	1309-37-1					
Benzyl alcohol	100-51-6					
calcium oxide	1305-78-8					
Solvent naphtha (petroleum), light arom.	64742-95-6					
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1					

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

#### 8.2 Exposure controls

**Personal Protection** 

**RESPIRATORY PROTECTION:** Breathing apparatus with filter.

EYE PROTECTION: Tightly fitting safety goggles.

**HAND PROTECTION:** rubber Glove thickness: 0.3 mm permeation rate according to EN 374: 3 (breakthrough time> 60 min) Nitrile rubber Glove thickness: 0.4 mm permeation rate according to EN 374: 2 (breakthrough time> 30 min)Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Ensure adequate ventilation, especially in confined areas.

# 9. Physical and Chemical Properties

#### 9.1 Information on basic physical and chemical properties Appearance:

Not determined

Not determined

**Physical State** Liquid Odor Slight

Odor threshold Not determined pН Not determined Melting point / freezing point (°C) Not determined Boiling point/range (°C) 136 - N.D.

Flash Point, (°C) >170

**Evaporation rate** Slower than ether Flammability (solid, gas) Not determined

Upper/lower flammability or explosive Not determined

limits

Vapour Pressure Not determined Vapour density Heavier than air Relative density 1.70 - 1.80 Solubility in / Miscibility with water Negligible Partition coefficient: n-octanol/water Not determined Auto-ignition temperature (°C) Not determined Decomposition temperature (°C) Not determined Viscosity Not determined **Explosive properties** 

9.2 Other information

Oxidising properties

VOC Content g/l:

Calculated grams of VOC per liter of coating product as applied. Specific Gravity (g/cm3) 1.736

## 10. Stability and Reactivity

## 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

#### 10.4 Conditions to avoid

Direct sources of heat.

## 10.5 Incompatible materials

Strong oxidizing agents.

#### 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

# 11. Toxicological Information

#### 11.1 Information on toxicological effects

**Acute Toxicity:** 

Oral LD50: No information available.

Inhalation LC50: No information available.

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

**Toxicity for reproduction:** No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	5000 mg/kg. oral, rat	>2000 mg/kg, rabbit	
100-51-6	Benzyl alcohol	1230 mg/kg rat, oral		1000 ppm / 8 hrs rat, inhalation
64742-95-6	Solvent naphtha (petroleum), light arom.	4700 mg/kg, oral, rat	>2000 mg/kg	3670 ppm/8 hours, rat, inhalation

#### Additional Information:

No Information

# 12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):No informationIC50 72hr (Algae):No informationLC50 96hr (fish):No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: No information

CAS-No.Chemical NameEC50 48hrIC50 72hrLC50 96hr28064-14-4phenol, polymer with formaldehyde, glycidyl etherNo informationNo informationNot available

7631-86-9	silicon dioxide (amorphous)	No information	No information	Not available
14808-60-7	quartz (silicon dioxide)	No information	No information	Not available
12034-12-7	sodium superoxide	No information	No information	No information
1309-37-1	red iron oxide	No information	No information	Not available
100-51-6	Benzyl alcohol	No information	No information	Not available
1305-78-8	calcium oxide	No information	No information	Not available
64742-95-6	Solvent naphtha (petroleum), light arom.	>1 - 10 mg/l	>1 - 10 mg/l	>10-100 mg/l
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	No information	No information	Not available

# 13. Disposal Considerations

**13.1 WASTE TREATMENT METHODS:** If recycling is not practicable, dispose of in compliance with local regulations. Waste codes should be assigned by the user based on the application for which the product was used. Empty containers should be taken to an approved waste handling site for recycling or disposal.

#### 14. Transport Information

**14.1 UN number** UN 3082

**14.2 UN proper shipping name** Environmentally Hazardous Substance, Liquid, N.O.S.

Technical name Not applicable

14.3 Transport hazard class(es) 9

Subsidiary shipping hazard Not applicable

14.4 Packing group

14.5 Environmental hazards Not applicable
14.6 Special precautions for user EmS-No.: Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

Not applicable

# 15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

**National Regulations:** 

Denmark Product Registration Number:

Not available

Not available

Danish MAL Code - Mixture: Not available

Sweden Product Registration Number: Not available

WGK Class: Not available

Trait oldos.

## 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

Not available

# 16. Other Information

# Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226 Flammable liquid and vapour.

**Norway Product Registration Number:** 

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eve damage. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H350 May cause cancer. H370 Causes damage to organs.

Causes damage to organs through prolonged or repeated exposure. H372

H411 Toxic to aquatic life with long lasting effects.

#### Reasons for revision

No Information

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

#### Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission European Union ΕU US United States

CAS Chemical Abstract Service

European Inventory of Existing Chemical Substances EINECS

Registration, Evaluation, Authorization of Chemicals Regulation REACH

Globally Harmonized System of Classification and Labeling of Chemicals GHS

LTEL Long term exposure limit Short term exposure limit STEL Occupational exposure limit OEL

Parts per million ppm

Milligrams per cubic meter ma/m3 TLV Threshold Limit Value

American Conference of Governmental Industrial Hygienists ACGIH

Occupational Safety & Health Administration OSHA

Permissible Exposure Limits PEL VOC Volatile organic compounds

Grams per liter a/1

mg/kg Milligrams per kilogram

N/A Not applicable Lethal dose at 50% LD50

Lethal concentration at 50% LC50

Half maximal effective concentration EC50 Half maximal inhibitory concentration IC50 Persistent bioaccumulative toxic chemical PBT vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

United Nations UN

International Maritime Dangerous Goods Code IMDG International Air Transport Association IATA

International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

International Bulk Container IBC Respiratory Tract Irritation RTI

Narcotic Effects NE

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.